



ASTREA SERIES

CARACTERISTICAS TECNICAS

MODELO	ANCHO LABOR	BRAZOS	SECCION BRAZO	DISTANCIA BRAZOS	SECCIÓN CHASIS	PROFUNDIDAD MAX.	DESPEJE	POTENCIA	CATEGORIA	RODILLO	PESO SIN RODILLO	PESO CON RODILLO
	M.	Nº	mm.	mm.	mm.	mm.	mm.	HP/CV		Ø	Kg.	Kg.
SS3 - NS - SS3R - NS	1,40	3	30x180	600	300x150x10	450	800	40/100	II	Ø 515	1150	1400
SS5 - NS - SS5R - NS	2,40	5	40x200	500	350x180x10	600	1000	90/160	II	Ø 515	1500	1750
SS7 - NS - SS7R - NS	3,20	7	40x200	470	350x180x10	600	1000	140/220	III	Ø 515	2000	2400
SS9 - NS - SS9R - NS	4,20	9	40x200	470	350x180x10	600	1000	200/300	III	Ø 600	2600	3100
SS11-NS - SS11R-NS	5,60	11	40x200	520	400x200x10	600	1000	300/400	III	Ø 600	3200	3900



SUBSOLADORES EN V HIDRONEUMATICOS



Gascón International
 Herederos de Manuel Gascón S.L.
 Tel. +34-974-21 87 20
 Fax. +34-974-21 87 21

info@gasconinternational.com

Gascon International

INTERNATIONAL OFFICES

Sra./Mrs. Małgarí Lagrasta
 Tel. +34 - 689 823 051
 Tel.Fax. +34 - 93-783 87 93

export@gasconinternational.com

Gascon.Export